

# KNAPP®-ADHESIVE

One-component polyurethane adhesives

**KNAPP®**  
connectors.com



+++ Solvent-free +++ Thixotropic – no drip +++ Coatable +++

**NEW**  
glass fiber  
reinforced

## KNAPP®-ADHESIVE PU+

*Fiber reinforced*

- I Glass Fiber Reinforced
- I High strength

## KNAPP®-ADHESIVE PU+

- I For smooth surfaces
- I Semi-hard adhesive joint

## KNAPP®-ADHESIVE PM+

- I Joint-filling for thick adhesive joints
- I Foams only lightly
- I Strong elastic adhesive joint

Very high bonding strength for end grain gluing. Can be subsequently powder-coated (30 min/+200°C).

Polyurethane adhesive - also suitable for sauna construction - Resistant to permanent temperatures up to 120°C.

By using spray mist, the curing time is reduced by 50%.

Art. No.	KNAPP®-ADHESIVE <b>PU+</b> Fiber reinforced (Z012)	KNAPP®-ADHESIVE <b>PU+</b> (Z011)	KNAPP®-ADHESIVE <b>PM+</b> (Z010)
<b>Application</b>	Craftsmanship, stairs, window, and door construction for universal assembly adhesives in industry and trade, renovations, and overhead installations.	From furniture to window production on smooth surfaces.	For assembly work on uneven surfaces.
<b>Properties</b>	Newly developed polyurethane-based construction adhesive, has a particularly force-reinforcing effect thanks to fiber-glass fibers, waterproof according to EN 204 class D4.	Easy to use one-component polyurethane adhesive, waterresistant according to EN 204 Class D4.	Easy to use, all purpose, one component polyurethane adhesive, joint-filling, waterresistant according to EN 204 class D4.
<b>Processing</b>	Apply on one side, swells during curing, skin forming time approx. 7 min, functional strength after approx. 20 min, curing time approx. 24 h, processing temperature min. +7 °C, material humidity <8%, bonding tests recommended.	Apply on one side, swells during curing, skin forming time approx. 10 min, functional strength after approx. 30 min, curing time approx. 24 h, processing temperature min. +7 °C, material humidity 8-14%, bonding tests recommended.	Apply on one side, swells during curing, skin forming time approx. 7 min, functional strength after approx. 20 min, curing time approx. 24 h, processing temperature min. +7 °C, material humidity 8-14%, bonding tests recommended.
<b>Materials</b>	Various wood and building materials and ceramics. Gluing of wood e.g. larch and metals e.g. aluminium, copper, brass, thermosets and thermoplastics. Colour: transparent-opaque.	Various types of wood and building materials, as well as plastics, stone, ceramics, metal and KNAPP® connectors, e.g. TREPPO (2-3 cartridges for 100 drill holes). Colour: beige.	A wide variety of wood materials, as well as plastics, stone, metal and all the recommended KNAPP® connectors. Colour: white.
<b>Bonding</b>	Apply to clean, grease- and dust-free surfaces. General processing instructions in the Technical and Safety Data Sheet for download.		



# KNAPP® 1K PUR ADHESIVE

Art. No.	Unit	Description
Z012	1 pc.	KNAPP®-ADHESIVE PU+ FIBER REINFORCED
Z012/10	10 pc.	KNAPP®-ADHESIVE PU+ FIBER REINFORCED
Z012/25	25 pc.	KNAPP®-ADHESIVE PU+ FIBER REINFORCED
Z011	1 pc.	KNAPP®-ADHESIVE PU+
Z011/10	10 pc.	KNAPP®-ADHESIVE PU+
Z011/25	25 pc.	KNAPP®-ADHESIVE PU+
Z010	1 pc.	KNAPP®-ADHESIVE PM+
Z010/10	10 pc.	KNAPP®-ADHESIVE PM+
Z010/25	25 pc.	KNAPP®-ADHESIVE PM+

KNAPP®-ADHESIVE PU+ is recommended for:

KNAPP®-DOWEL



DEKCLICK




CHAMP



CLIPS



miniKLiCK



KNAPP®-ADHESIVE PM+ is recommended for:  
the TREPPO system



KNAPP®-ADHESIVES are also  
included in the following boxes:



KNAPP® DOWEL Box



DEKCLICK® Box



CLASSIC Box



TREPPO Box



online-store

[www.knapp-connectors.com/en](http://www.knapp-connectors.com/en)

Our online shop is open  
24/7 and offers you  
maximum flexibility.

Delivery within the EU  
is usually within 4 to 5  
working days.

Place your  
order online  
or contact us



Phone



Videocall



E-Mail



On site

More info & newsletter  
on our website!

Knapp GmbH | Wassergasse 31 | A-3324 Euratsfeld | Tel.: +43 (0)7474 / 799 10 | Fax: +43 (0)7474 / 799 10 99

Knapp GmbH | Vertrieb Deutschland | Föhrenweg 1 | D-85591 Vaterstetten  
Tel.: +49 (0)8106 / 99 55 99 0 | E-Mail: [info@knapp-connectors.com](mailto:info@knapp-connectors.com) | [www.knapp-connectors.com/en](http://www.knapp-connectors.com/en)



YouTube



online-store